BONDERITE

Technical Data Sheet

BONDERITE C-SO 101

Known as P3-solvclean 101
February 2022

PRODUCT DESCRIPTION

BONDERITE C-SO 101 provides the following product characteristics:

Technology	Industrial Cleaner
Product Type	Solvent Based Cleaner
Application	Parts Cleaning

BONDERITE C-SO 101 is a quick drying solvent mixture without emulsifier and bad smell.

Application Areas:

- Dielectric cleaner.
- Typical applications include also component cleaning in electric motors.
- Cleaning of stationary machines and parts, soiled with oil, in repair shops and production plants.
- Removal of protective coatings at motor cars.
- Removal of tar spots at motor cars.

Composition:
Solvent mixture without bad smell, dries without leaving residues, free of ingredients (CKW, FCKW etc.) that have to be labelled.

TECHNICAL DATA

Appearance	clear, colorless, homogeneous liquid
Density, g/mL	0.77
Viscosity	1.8 cSt / 25°C
Evaporation number (DIN 53170)	~88 (for the product as it is)
Flash Point:	~57 °C (does not sink)
Solubility:	with water only mixable by force (e. g. with injector)
Melting Point, °C	-30
Boiling Point, °C	180
Dielectric strength, kV/2.5 mm (UNE EN 60156:97, average value)	70

DIRECTIONS FOR USE

Preliminary Statement:
Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application:
1. The parts to be cleaned can be treated manually (with soaked sponge) or in a dip bath. BONDERITE C-SO 101 evaporates quickly after the cleaning.

2. BONDERITE C-SO 101 can be applied undiluted with the help of a spray equipment or manually with a sponge. During the application time the treated areas should be treated with a rag or sponge and afterwards must be sprayed off with water. BONDERITE C-SO 101 can be applied with a water jet.

3. BONDERITE C-SO 101 can be applied with the help of a spray equipment or manually.
After a short application time it should be washed off with additional BONDERITE C-SO 101.

Application Concentration:
As concentrate for the use in water jets:

BONDERITE C-SO 101: water = 1 : 50 to 1 : 20 (at an consumption of 5 pails water at least 1 L BONDERITE C-SO 101 must be consumed simultaneously).

Application temperature:

Room temperature, in water jets with water of 80 °C.

Application Time:

Dependent on the extent of soiling of the parts to be cleaned resp. on the thickness of the protective coating.

Classification:
Please refer to the corresponding **Safety Data Sheet** for details on:

- **Hazards identification**
- **Transport information**
- **Regulatory information**

Storage:

Recommended Storage Temperature, °C	0 to 40
Shelf-life, months (in unopened original packaging)	24

Sapony

Henkel

ADDITIONAL INFORMATION

Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:
In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:
The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.
Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:
The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage
Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.1

Sapiony X

Henkel AG & Co. KGaA
40191 Düsseldorf, Germany
Phone: +49-211-797-0

Henkel Corporation USA
Madison Heights, MI 48071
Phone: +1-248-583-9300

Henkel (China) Co. Ltd.
201203 Shanghai, China
+86.21.2891.8000

For more information, please contact us on www.henkel.com

This document was created and digitally signed by Henkel at 2025-06-30T17:22:27.971Z